

6x4 ISUZU flatbed tow truck with 10 tons Knuckle crane

PART I: Details showing

Complete Vehicle Parameter	
Vehicle	Flat tow truck
Overall dimensions (mm)	11000×2550×3800
Flatbed size (mm)	7200×2550
Gross Vehicle Weight (kg)	Appro × 35000
Net weight (kg)	Appro × 20000
Flatbed towing weight (kg)	Appro × 15000
Rear Boom towing weight (kg)	Appro × 15000
Wheel base (mm)	4600+1370
Max speed (Km/h)	100
Front/Rear axle loading capacity	9T/26T
Standard configuration	- 15 tons hydraulic winch 1 set - Auxiliary wheel 2pcs - Rear towing boom assembly 1 set (15tons) - Steel wire rope 45m - Bundle belt 4pcs - Rear tail lights LED,both sides electronic lights. - Tool box
Special performance	1. Towing two vehicle. 2. Hydraulic operation lever control flatbed and carriage arm. 3. Winch speed : 8m/min. 4. Flatbed minimum tilt angle: 8°
Chassis Parameter	
Cabin	Single row cabin, power steering, air conditioner, 2-3 passengers,left hand drive.
Traction system	6x4
Engine	Brand: ISUZU Model: 6UZ1-TCG61, 380hp

	Fuel type: diesel Displacement: 9839ml Emission standard : Euro IV
Transmission	FAST 12 forward,1 reverse, manual operated
Tire model	315/80R22.5
No.of tires	10pcs, and a spare tire
Technical parameter of crane	
Crane Model	China brand 10Tons Knuckle Crane with Front and rear hydraulic outriggers and high altitude seat
Crane Weight	3400kg
Max. Lifting capacity	10000kg
Max lifting height	14.4M
Working radius	11.4M
Rotation angle	360° All rotation
Remarks	1. Color is optional 2. Customized LOGO painting as per customer request